

## TECHNICAL CHARACTERISTICS

**HEM**

| REFERENCE                     | FS3510M                                        |                                                                            |
|-------------------------------|------------------------------------------------|----------------------------------------------------------------------------|
| OUTPUT                        | AC Output Power (kVA/kW) @50°C <sup>[1]</sup>  | 3510                                                                       |
|                               | AC Output Power (kVA/kW) @40°C <sup>[1]</sup>  | 3630                                                                       |
|                               | Operating Grid Voltage (VAC) <sup>[2]</sup>    | 34.5kV ±10%                                                                |
|                               | Operating Grid Frequency (Hz)                  | 50Hz/60Hz                                                                  |
|                               | Current Harmonic Distortion (THDi)             | < 3% per IEEE519                                                           |
|                               | Power Factor (cosine phi) <sup>[3]</sup>       | 0.5 leading ... 0.5 lagging adjustable / Reactive Power injection at night |
| INPUT                         | MPPT @full power (VDC)                         | 934V-1310V                                                                 |
|                               | Maximum DC voltage                             | 1500V                                                                      |
|                               | Number of PV inputs <sup>[2]</sup>             | Up to 36                                                                   |
|                               | Number of Freemaq DC/DC inputs                 | Up to 6                                                                    |
|                               | Max. DC continuous current (A)                 | 3970                                                                       |
|                               | Max. DC short circuit current (A)              | 6000                                                                       |
| EFFICIENCY & AUXILIARY SUPPLY | Efficiency (Max) (η)                           | 98% including MV transformer (preliminary)                                 |
|                               | CEC (η)                                        | 98% including MV transformer (preliminary)                                 |
|                               | Max. Power Consumption (KVA)                   | 20                                                                         |
| CABINET                       | Dimensions [WxDxH] (ft)                        | 21.7 x 7 x 7                                                               |
|                               | Dimensions [WxDxH] (m)                         | 6.6 x 2.2 x 2.2                                                            |
|                               | Weight (lb)                                    | 30865                                                                      |
|                               | Weight (kg)                                    | 14000                                                                      |
|                               | Type of ventilation                            | Forced air cooling                                                         |
| ENVIRONMENT                   | Degree of protection                           | NEMA 3R - IP54                                                             |
|                               | Permissible Ambient Temperature                | -35°C to +60°C / >50°C Active Power derating                               |
|                               | Relative Humidity                              | 4% to 100% non condensing                                                  |
|                               | Max. Altitude (above sea level) <sup>[4]</sup> | 2000m                                                                      |
|                               | Noise level <sup>[5]</sup>                     | < 79 dBA                                                                   |
| CONTROL INTERFACE             | Interface                                      | Graphic Display                                                            |
|                               | Communication protocol                         | Modbus TCP                                                                 |
|                               | Plant Controller Communication                 | Optional                                                                   |
|                               | Keyed ON/OFF switch                            | Standard                                                                   |
| PROTECTIONS                   | Ground Fault Protection                        | GFDI and Isolation monitoring device                                       |
|                               | General AC Protection                          | MV Switchgear (configurable)                                               |
|                               | General DC Protection                          | Fuses                                                                      |
|                               | Overvoltage Protection                         | AC, DC Inverter and auxiliary supply type 2                                |
| CERTIFICATIONS                | Safety                                         | UL1741, CSA 22.2 No.107.1-01, UL62109-1, IEC62109-1, IEC62109-2            |
|                               | Compliance                                     | NEC 2014 / NEC 2017 (optional)                                             |
|                               | Utility interconnect                           | IEEE 1547.1-2005 / UL1741SA-Sept. 2016                                     |

[1] Values at 1.00•Vac nom and cos Φ= 1.

Consult Power Electronics for derating curves.

[2] Consult Power Electronics for other configurations.

[3] Consult P-Q charts available:  $Q(kVar)=\sqrt{(S(kVA))^2-P(kW)^2}$ .

[4] Consult Power Electronics for other altitudes.

[5] Readings taken 1 meter from the back of the unit.