

# SolarEdge CSS-OD

## Battery Cabinet 197 kWh

## Battery Inverter 50 / 100 kW

CSS-OU-197 / PCS050

10  
YEAR  
WARRANTY



## High power energy storage for on-grid commercial and industrial solar

### • Easy installation and deployment

- Pre-assembled and factory-tested cabinet for quick setup
- Compact cabinet that can be installed indoors or outdoors, with a top-lifting eye bolt solution
- Customize AC-coupled sites with 1 or 2 x 50 kW inverters per battery, and scale up to 4 MWh\* storage capacity

### • Optimized storage savings

- Powered by SolarEdge ONE for C&I that is designed to optimize site energy production, storage, and consumption constantly
- Multiple storage optimization modes supported, including maximized self-consumption, peak shaving, tariff optimization, export and import limits\*\*

### • Built-in safety and resilience

- Integrated fire detection and double fire suppression mechanism, with a fire-fighting water inlet
- Built-in safeguards: earth fault, leakage fault, integrated DC & AC surge protection, and an explosion relief panel
- Reverse polarity protection mechanism
- Acoustic-visual alarm
- Multi-sensor security: flood, door, CO, smoke, heat, and humidity sensors

### • Single trusted vendor

- PV and storage system from a single vendor
- One source for warranty, support, and training
- 10-year product and performance warranty

\* Up to 1 MW active power output

\*\* Some optimization features may not be available in all regions. Possible savings may vary by country, depending on applicable tariffs and site/installation conditions.

# SolarEdge CSS-OD

## Battery Cabinet 197 kWh

### CSS-OU-197

BATTERY CABINET 197 kWh	CSS-OU-197	Units
<b>TECHNICAL SPECIFICATIONS</b>		
Cell Chemistry	LFP	
Total Battery Capacity	197.12	kWh
Usable Battery Capacity	187.15	kWh
Battery Module Total Capacity	17.92	kWh
Number of Modules	11	
Maximum C-Rate (charge/discharge)	0.5	C-rate
DC Voltage Range	616 - 792	V <sub>dc</sub>
AC Auxiliary Input <sup>(1)</sup>	220+/-15% /50 220+/-10% /60	V <sub>ac</sub> / Hz
<b>MECHANICAL SPECIFICATIONS</b>		
Battery Cabinet Dimensions (W x D x H)	1300 x 1200 x 2360	mm
Battery Cabinet Weight	2360	kg
IP Protection	IP54	
Corrosion Protection	C4	
Cooling Method	Built-in HVAC	
Noise <sup>(2)</sup>	<70	dBA
<b>STANDARDS COMPLIANCE</b>		
Safety	IEC 62619, including 7.3.3, UL9540A	
Ingress Protection	IEC 60529	
Transportation	UN 38.3	
Emissions	EN / IEC 61000-6-2 EN / IEC 61000-6-4	
<b>ENVIRONMENTAL SPECIFICATIONS</b>		
Operating Temperature <sup>(3)</sup>	-30 to +50 (>45 derating)	°C
Operating Humidity	5 to 95 (non-condensing)	%
Maximum Operating Altitude	3000	m
<b>SAFETY</b>		
Fire Safety	Heat & humidity detectors	
	Photoelectric smoke detector	
	Cabinet level 2×aerosol + support external water pipe	
Electrical Safety	Energy Module integrated with NOVEC 1230	
	Reverse polarity protection	
	Earth fault and leakage fault detection	
Operator Safety	AC and DC surge protection	
	Toxic gas detector (CO)	
Emergency Power-Off Pushbutton	Integrated	
Flood Detector	Integrated	
Door Contact Switch	integrated	
Pressure Relief Valves and Deflagration Panels	integrated	
<b>TRANSPORTATION</b>		
Forklift	Integrated support for forklift forks >5000	kg
Crane	Four eye bolts supplied	
<b>WARRANTY<sup>(4)</sup></b>		
System	10 years	
Performance	7000 cycles or 10 years up to 70% SoH	

(1) Single-phase power is required for the Battery Cabinet HVAC operation.

(2) Measured one meter from a CSS-OD Battery Cabinet Battery with a single Inverter.

(3) Power derating may apply within the range of -30 to -10 °C.

(4) For warranty details, conditions, and exclusions, refer to the Limited Product Warranty for SolarEdge CSS-OD.

# / SolarEdge CSS–OD

## Battery Inverter 50 kW

### PCS050

BATTERY INVERTER 50 kW <sup>(5)</sup>	PCS050	Units
<b>AC SPECIFICATIONS</b>		
Rated AC Active Power Output	50	kW
Maximum AC Apparent Output Power	55	kVA
Maximum Continuous Output Current (per phase)	80	A <sub>ac</sub>
Maximum Inverter Efficiency	97.5%	
AC Output Voltage – Line to Line / Line to Neutral (Nominal)	400 / 230	V <sub>ac</sub>
AC Output Voltage – Line to Line / Line to Neutral (Range)	340 – 440	V <sub>ac</sub>
AC Frequency	50 / 60 ± 5	Hz
AC Line <sup>(6)</sup>	3W + PE / 4W + PE	
Total Harmonic Distortion	<3	%
Power Factor Range	-1 to 1 / leading, lagging	
Number of Battery Inverters per Battery Cabinet 197 kWh	1 or 2	
<b>DC SPECIFICATIONS</b>		
Maximum DC Input Power	55	kW
Maximum DC Current	55 x 2	Adc
Number of DC Input Interfaces	2	
<b>SAFETY FEATURES</b>		
Reverse Polarity Protection	Yes	
Grid Monitoring	Yes	
Earth Fault Protection	Yes	
Earth Leakage Protection	Yes	
DC Surge Protection	Type II integrated	
AC Surge Protection	Type III integrated	
<b>COMMUNICATION</b>		
Communication Ports	RS-485 / CAN	
<b>MECHANICAL SPECIFICATIONS</b>		
Inverter Dimensions (W x D x H)	650 x 324 x 715	mm
Inverter Weight	68	kg
IP Protection	IP65	
Cooling Method	Air Cooling	
AC Input Cable Cross Section <sup>(7),(8)</sup> / Lugs Size	25 to 35 mm <sup>2</sup> / M6	
<b>STANDARD COMPLIANCE</b>		
Safety	IEC 62109-1, IEC 62109-2, IEC 62477-1	
Emissions	IEC 61000-6-4, IEC 61000-3-11, EN/IEC 61000-3, CISPR 11	
Grid Connection	NRS 097-2-1:2017 Edition 2.1, NRS 097-2-1:2024 Edition 3, CEI-016, CEI 0-21 VDE AR-N-4105, VDE AR-N 4110 EN 50549-1/10, RfG, NC RfG, PTPIREE UNE 217002, NTS V2.1	
<b>ENVIRONMENTAL SPECIFICATIONS</b>		
Operating Temperature	-20 to +45	°C
Operating Humidity	5 to 95 (non-condensing)	%
Maximum Operating Altitude	3000	m
<b>WARRANTY<sup>(9),(10)</sup></b>		
System	10 years	

(5) It is required to have an AC-coupled SolarEdge PV system at the site.

(6) Compatible with both Delta/WYE grid types.

(7) Only copper cables should be used.

(8) It is recommended to use flexible conductors: multi-stranded, class 6.

(9) For warranty details, conditions, and exclusions, refer to the Limited Product Warranty for SolarEdge CSS-OD

(10) The Battery inverter cannot be directly used to connect life support equipment and medical equipment.