



# IQ8H-208 Microinverter

Our newest IQ8 Microinverters<sup>1,2,3</sup> are the industry's first microgrid-forming<sup>4</sup>, software-defined microinverters with split-phase power conversion capability to convert DC power to AC power efficiently.



Key specifications	IQ8H-208-72-2-US
Peak output power	366 VA
Nominal grid voltage (L-L)	208 V, single-phase (L-L), 120°
Nominal frequency	60 Hz
CEC weighted efficiency	97%
Maximum input DC voltage	60 V
MPPT voltage range	36-45 V
Maximum module $I_{sc}$	20 A
Ambient temperature range	-40°C to 60°C (-40°F to 140°F)



## Simple

- Lightweight and compact with plug-and-play connectors
- Power line communication (PLC) between components
- Faster installation with simple two-wire cabling

## Reliable

- More than one million cumulative hours of testing
- Industry-leading limited warranty of up to 25 years
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

## Microgrid-forming

- Complies with the latest advanced grid support<sup>4</sup>
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets CA Rule 21 (UL 1741-SA) and IEEE 1547:2018 (UL 1741-SB 3<sup>rd</sup> Ed.)

<sup>1</sup> IQ8 Series Microinverters can be added to existing IQ7 systems on the same IQ Gateway only in the following grid-tied configurations: Solar Only or Solar + Battery (IQ Battery 3T/10T and IQ Battery 5P) without backup.

<sup>2</sup> IQ7 Series Microinverters cannot be added to a site with existing IQ8 Series Microinverters on the same gateway. Mixed system of IQ7 and IQ8 will not support IQ8-specific PCS features and grid-forming capabilities.

<sup>3</sup> IQ Microinverters ship with default settings that meet North America's IEEE 1547 interconnection standard requirements. Region-specific adjustments may be requested by an Authority Having Jurisdiction (AHJ) or utility representative, according to the IEEE 1547 interconnection standard. Use an IQ Gateway to make these changes during installation.

<sup>4</sup> IQ8H-208 operates only in grid-tied mode. IQ8H-208 supports single-phase, 208 V only.

Input data (DC)	Units	IQ8H-208-72-2-US <sup>5</sup>
Commonly used module pairings <sup>6</sup>	W	295–500
Module compatibility	—	To meet compatibility, PV modules must be within the following maximum input DC voltage and maximum module $I_{sc}$ . Module compatibility can be checked at <a href="https://enphase.com/installers/microinverters/calculator">https://enphase.com/installers/microinverters/calculator</a> .
MPPT voltage range	V	36–45
Operating range	V	16–58
Minimum/Maximum start voltage	V	22/58
Maximum input DC voltage	V	60
Maximum continuous input DC current	A	12
Maximum input DC short-circuit current	A	25
Maximum module $I_{sc}$	A	20
Overvoltage class DC port	—	II
DC port backfeed current	mA	0
PV array configuration	—	Ungrounded array; no additional DC side protection required; AC side protection requires a maximum of 20 A per branch circuit
Output data (AC)	Units	IQ8H-208-72-2-US <sup>5</sup>
Peak output power	VA	366
Maximum continuous output power	VA	360
Nominal voltage (L-L)	V	208, single-phase (L-L), 120°
Minimum and maximum grid voltage <sup>7</sup>	V	183–229
Maximum continuous output current	A	1.73
Nominal frequency	Hz	60
Extended frequency range	Hz	47–68
AC short-circuit fault current over three cycles	A <sub>rms</sub>	4.4
Maximum units per 20 A (L-L) branch circuit <sup>8</sup>	—	9
Total harmonic distortion	%	<5
Overvoltage class AC port	—	III
AC port backfeed current	mA	30
Power factor setting	—	1.0
Grid-tied power factor (adjustable)	—	0.85 leading ... 0.85 lagging
Peak efficiency	%	97.5
CEC weighted efficiency	%	97
Nighttime power consumption	mW	15
Mechanical data		IQ8H-208-72-2-US <sup>5</sup>
Ambient temperature range		–40°C to 60°C (–40°F to 140°F)
Relative humidity range		4% to 100% (condensing)

<sup>5</sup> IQ8H-208 operates in grid-tied mode only at 208 VAC.

<sup>6</sup> No enforced DC/AC ratio.

<sup>7</sup> Nominal voltage range can be extended beyond nominal if required by the utility.

<sup>8</sup> Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

Mechanical data	IQ8H-208-72-2-US <sup>5</sup>
DC connector type	MC4
Dimensions (H × W × D)	212 mm (8.3") × 175 mm (6.9") × 30.2 mm (1.2")
Weight	1.08 kg (2.38 lb)
Cooling	Natural convection—no fans
Approved for wet locations	Yes
Pollution degree	PD3
Enclosure	Class II double-insulated, corrosion-resistant polymeric enclosure
Environmental category/UV exposure rating	NEMA Type 6/Outdoor
Compliance	IQ8H-208-72-2-US <sup>5</sup>
Certifications	<p>CA Rule 21 (UL 1741-SA), UL 62109-1, IEEE 1547:2018 (UL 1741-SB 3<sup>rd</sup> Ed.), FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01.</p> <p>This product is UL Listed as PV rapid shut down equipment and conforms with NEC 2014, NEC 2017, NEC 2020, and NEC 2023 section 690.12 and C22.1-2018 Rule 64-218 rapid shutdown of PV systems, for AC and DC conductors, when installed according to the manufacturer's instructions.</p>

# Components of the Enphase Energy System



## **IQ Battery**

All-in-one AC-coupled storage solution that integrates seamlessly with your solar energy system, providing reliable backup power and intelligent energy management for maximum performance and energy savings.



## **IQ System Controller**

The IQ System Controller connects the home to the grid power, IQ Batteries, generator and solar PV with microinverters.



## **IQ Combiner/IQ Gateway**

The IQ Combiner/IQ Gateway is a device that performs energy management, provides internet connectivity, and integrates with the IQ Series Microinverters to provide complete control and insights into the Enphase Energy System.



## **IQ Cable**

The IQ Cable is a continuous-length 12-AWG cable with pre-installed connectors for IQ Microinverters that support faster, simpler, and more reliable installations. The cable is handled like standard outdoor-rated electrical wire, allowing it to be cut, spliced, and extended as needed.

# Revision history

Revision	Date	Description
DSH-00242-3.0	December 2024	Updated information on backward compatibility with IQ7 Series Microinverters.
DSH-00242-2.0	February 2024	Updated the information about IEEE 1547 interconnection standard requirements.
DSH-00242-1.0	November 2023	Updated the module compatibility specification. Updated the nighttime power consumption value. Included NEC 2023 specification in the "Compliance" section.

Previous releases.