



DC/AC MODIFIED SINE WAVE INVERTER

	CHNB-X500-212	CHNB-X500-224
OUTPUT	RATED POWER	500W
	SURGE POWER	1000W
	AC VOLTAGE	220/230/240AC ±3%
	WAVEFORM	MODIFIED SINE WAVE
	FREQUENCY	50Hz±3%
	WAVE DISTORTION	5%
	USB PORT	5V 2A
INPUT	DC VOLTAGE	12v
	VOL. RANGE	10-15VDC
	UNLOAD CURRENT	<0.3A
	EFFICIENCY	>85%
	DC CONNECTION	Cables with clips & cigarette lighter
PROTECTION	LOW VOL. ALARM	10VDC+/-0.5V
	LOW VOL. SHUT DOWN	9.5VDC+/-0.5V
	OVERLOAD PROTECTION	shut off output
	OVER VOL. SHUT DOWN	15.5V
	FAN cooling	when heat arrive 45℃±5℃, fan will begin working
	OVERHEAT PROTECTION	85℃, shut off output automatically
PACKAGE	PRODUCT SIZE (MM)	246*100*60mm
	PACKING SIZE(MM)	370*307*390mm
	NET W. (kgs)	970G
	GROSS W. (kgs)	1211G

