



JF SOLAR



M10 Mono Half Cell Module

JFS2-132-18X
475~495W

JFS2-132-475M
JFS2-132-480M
JFS2-132-485M
JFS2-132-490M
JFS2-132-495M

IEC61215/IEC61730

ISO9001:Quality Management System ISO14001:Environmental Management System

ISO45001:Occupational Health and Safety Management System



Higher Power Output



Better Low-light
Performance




MBB Half Cut Cell With
PERC Technology



Less Shading Effect




0~+5W Positive
Tolerance



PID Resistance

12-year Warranty for Materials and Processing;
25-year Warranty for Extra Linear Power Output



-0.55%

25-year Power
Warranty Annual
Power Attenuation
-0.55%

- Additional value from JF Solar's linear warranty
- Standard performance warranty

Anhui JF Solar Technology Co., Ltd

TEL:0555-5510000

WEB:www.jf-solartech.com

E-mail:info@jf-solartech.com

ADD:No.9 ,West Taiyanghe Road,He County Economic Development Zone,Maanshan City,Anhui Province,China


M10 Mono Half Cell (6×22) Mono Solar Module

Module Type		JFS2-132-475M		JFS2-132-480M		JFS2-132-485M		JFS2-132-490M		JFS2-132-495M	
Test Environment		STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power	Pmax(W)	475	354.7	480	358.5	485	362.2	490	365.9	495	369.7
Open Circuit Voltage	Voc(V)	44.80	41.92	44.95	42.06	45.10	42.20	45.25	42.34	45.40	42.48
Short Circuit Current	Isc(A)	13.51	10.92	13.59	10.98	13.67	11.05	13.74	11.11	13.82	11.17
Maximum Power Voltage	Vm(V)	37.63	35.08	37.93	35.22	37.93	35.36	38.08	35.50	38.23	35.64
Maximum Power Current	Im(A)	12.63	10.11	12.79	10.18	12.79	10.24	12.87	10.31	12.95	10.37
Module Efficiency	(%)	20.2		20.4		20.6		20.9		21.1	
Tolerance	(W)	0~+5									
Cell Type	(mm)	182×182									
Number of Cells	(Pcs)	132 (6×22)									
Maximum System Voltage	(V)	1500V(IEC)									
Temp. Coeff. of Voc	(%/°C)	-0.270									
Temp. Coeff. of Isc	(%/°C)	0.048									
Temp. Coeff. of Pm	(%/°C)	-0.350									
OperatingTemperature	°C	-40 to 85									
Nominal Operating Cell Temperature (NOCT)	°C	45±2									
Max. Series Fuse	(A)	25									
Pressure Bearing	(Pa)	5400									
Wind Bearing	(Pa)	2400									

STC: Irradiance 1000W/m², Cell temperature 25°C, AM1.5

NOCT: Irradiance 800W/m², Ambient temperature 20°C, Wind speed 1m/s

ENGINEERING DRAWINGS




Manufactured in China

MATERIAL DETAILS


Frame	Anodized aluminum alloy frame
Glass	Double glass, 2.0mm tempered glass
Cell	6×22 mono solar cell
Junction Box	IP ₆₈ , TÜV & UL
Diode Quantity	3
Cable&Connector	4mm ² EVO2 or EVO2 compatible
Cable Length	300mm or as customer's requirements

IV CURVES

Current-Voltage Curve (JFS2-132-18X)



Power-Voltage Curve (JFS2-132-18X)



PACKING DETAILS

Dimension	(mm)	2073×1133×35
Weight	(kg)	30.1
Loading Capacity	155pcs/20GP 682pcs/40HC	
Packing	Pcs/pallet	31